

Outside Micrometers with Interchangeable Anvils


Series 104

This Outside Micrometer offers you an extra wide measuring range with the following benefits:

- Easy, interchangeable anvils allow a wide range of measurements.



104-171



104-135A

Metric

No.	Range [mm]	Graduation	Max. Permissible Error E MPE	Variation in length V MPE	Measuring force [N]	Setting standard	Interchangeable anvils	Mass [kg]
104-171	0-50	0,01 mm	±5 µm	2 µm	5-10	1 (25 mm)	1	0,32
104-135A	0-150	0,01 mm	±6 µm	3 µm	5-10	5 (25, 50, 75, 100, 125 mm)	6	1,35
104-140A	100-200	0,01 mm	±7 µm	4 µm	5-10	4 (100, 125, 150, 175 mm)	4	1,38
104-136A	150-300	0,01 mm	±8 µm	5 µm	5-10	6 (150, 175, 200, 225, 250, 275 mm)	6	2,65
104-142A	300-400	0,01 mm	±10 µm	6 µm	10-14	4 (300, 325, 350, 375 mm)	4	3,31
104-143A	400-500	0,01 mm	±11 µm	7 µm	10-14	4 (400, 425, 450, 475 mm)	4	4,81
104-144A	500-600	0,01 mm	±12 µm	8 µm	10-14	4 (500, 525, 550, 575 mm)	4	6,35
104-145A	600-700	0,01 mm	±14 µm	9 µm	10-14	4 (600, 625, 650, 675 mm)	4	7,72
104-146A	700-800	0,01 mm	±15 µm	10 µm	10-14	4 (700, 725, 750, 775 mm)	4	9,08
104-147A	800-900	0,01 mm	±16 µm	11 µm	10-14	4 (800, 825, 850, 875 mm)	4	10,41
104-148A	900-1000	0,01 mm	±18 µm	12 µm	10-14	4 (900, 925, 950, 975 mm)	4	11,78