(

## Holtest SERIES 368 — Three-point/Two-point Internal Micrometers

## Non-Interchangeable-Head Sets



368-906

368-907

368-912

Metric Inch								
Set Order No.	Range* (mm)	Graduation (mm)	Content of Set		Set Order No.	Range* (in)	Graduation (in)	Content of Set
(Two-point) 368-906	2 - 3	0.001	Micrometer head unit   2 - 2.5 mm 1 pc.   2.5 - 3 mm 1 pc.   Setting ring (ø2.5) 1 pc.   Hex wrench 1 pc.		(Two-point) 368-926	0.08 - 0.12	0.0001	Micrometer head unit   0.08 - 0.1 in 1 pc.   0.1 - 0.12 in 1 pc.   Setting ring (0.1 in DIA.) 1 pc.   Hex wrench 1 pc.
368-907	3 - 6		Micrometer head unit   3 - 4 mm 1 pc.   4 - 5 mm 1 pc.   5 - 6 mm 1 pc.   Setting ring (ø4, ø5) 1 pc. each   Hex wrench 1 pc.		368-927	0.12 - 0.28		Micrometer head unit 1 pc.   0.12 - 0.16 in 1 pc.   0.16 - 0.2 in 1 pc.   0.2 - 0.24 in 1 pc.   0.24 - 0.28 in 1 pc.   Setting ring 1 pc. each   (0.16 in DIA, 0.24 in DIA.) Hex wrench
(Three-point) <b>368-911</b>	6 - 12		Micrometer head unit 1   6 - 8 mm 1 pc.   8 - 10 mm 1 pc.   10 - 12 mm 1 pc.   setting ring (ø8, ø10) 1 pc.   Setting ring (ø8, ø10) 1 pc.   Extension rod (100 mm) 1 pc.   Spanner 2 pcs.   Hex wrench 1 pc.		(Three-point) 368-916	0.275 - 0.5		Micrometer head unit 0.275 - 0.35 in 1 pc   0.35 - 0.425 in 1 pc 0.35 - 0.425 in 1 pc   0.425 - 0.5 in 1 pc 1 pc each   (0.35 in DIA, 0.5 in DIA, 1 pc. each 1 pc each   Setting ring 1 pc. 5 in DIA, 0.5 in DIA, 1 pc each   Ketnesion rod (100 mm) 1 pc ket wrench 1 pc
368-912	12 - 20	0.005	Micrometer head unit   12 - 16 mm 1 pc.   16 - 20 mm 1 pc.   Setting ring (ø16) 1 pc.   Extension rod (150 mm) 1 pc.   Spanner 2 pcs.   Hex wrench 1 pc.		368-917	0.5 - 0.8	0.0002	Micrometer head unit 1 pc.   0.5 - 0.65 in 1 pc.   0.65 - 0.8 in 1 pc.   Setting ring (0.65 in DIA.) 1 pc.   Extension rod (150 mm) 1 pc.   Spanner 2 pcs.   Hex wrench 1 pc.

\* The measurement range cannot be enlarged by measuring heads that are not standard-supplied (the accuracy is not guaranteed).

Mitutoyo