

## Measurement Data Wireless Communication System U-WAVE-TMB/TCB (Mitutoyo Bluetooth® U-WAVE)

### Transmitter/Receiver



### SPECIFICATIONS

Order No.	For Digimatic micrometers		For Digimatic calipers	
	264-626	264-627	264-624	264-625
Model	<b>U-WAVE-TMB</b> (IP67 type dust/water-proof)	<b>U-WAVE-TMB</b> (buzzer type)	<b>U-WAVE-TCB</b> (IP67 type dust/water-proof)	<b>U-WAVE-TCB</b> (buzzer type)
Protection level	IP67	N/A	IP67	N/A
Data reception indication	LED	LED, buzzer	LED	LED, buzzer
Power supply	Lithium battery CR2032×1			
Battery life	Approx. 1 year under normal conditions of use, but varies according to usage.			
Mass (g)	18			

For model compatibility information, refer to "U-WAVE fit Compatible Devices", a separate sheet provided with **Catalog No. E12000**: Measurement Data Wireless Communication System U-WAVE.  
[https://www.mitutoyo.co.jp/support/service/catalog/09\\_system/1200\\_appendix.pdf](https://www.mitutoyo.co.jp/support/service/catalog/09_system/1200_appendix.pdf)



02AZF310



02AZF300

Choose a connecting unit compatible with your gage.

Order No.	02AZF310	02AZF300
Protection level	IP67	N/A
Mass (g)	6	
Connecting unit	<b>U-WAVE-TMB/TCB</b> (for dust/water-proof type)	<b>U-WAVE-TCB</b> (for standard type)

Note: Water-proof performance is ensured only when attached to measuring instruments of IP67 type.

### Compatibility of measuring tool and unit

	Assembled appearance	Connecting unit	Transmitter
For micrometers	Standard	02AZF310	<b>264-627 U-WAVE-TMB</b> (buzzer type)
	Water-proof type	02AZF310	<b>264-626 U-WAVE-TMB</b> (IP67 type dust/water-proof)
For calipers	Standard	02AZF300	<b>264-625 U-WAVE-TCB</b> (buzzer type)
	Coolant-proof type	02AZF310	<b>264-624 U-WAVE-TCB</b> (IP67 type dust/water-proof)