MeasurLink® ENABLED **U-WAVE** fit

V-Anvil Micrometers SERIES 314 — 3 Flutes and 5 Flutes

- Measures the outside diameter of taps and reamers with an odd number of flutes.
- Measures pitch diameter: refer to "Quick Guide to Precision Measuring Instruments" on page B-80.
- Measuring faces: Carbide.
- Equipped with Ratchet Stop for constant measuring force.



SPECIFICATIONS

SI ECII IC/ (IIOII)						
Metric		For 3-flute cutting tools				
Order No.	Range (mm)	Resolution (mm)	Maximum permissible error J _{MPE} (µm)	Anvil	Remarks	
Digimatic (LCD)						
314-251-30	1 - 15	0.001	±4		w/groove	
314-252-30	10 - 25				w/groove	
314-253-30	25 - 40		±5	60°	_	
314-261-30	1 - 15		±4		_	
314-262-30	10 - 25					

Inch/Metr	ic	For 3-flut	For 3-flute cutting tools			
Order No.	Range (in)	Resolution	Maximum permissible error JMPE (in)	Anvil	Remarks	
Digimatic (LCD)						
314-351-30	0.05 - 0.6	0.00005 in/	±0.0002	60°	w/groove	
314-352-30	0.4 - 1				W/ gloove	
314-353-30	1 - 1.6		±0.00025		_	
314-361-30	0.05 - 0.6	0.001 111111	±0.0002		_	
314-362-30	0.4 - 1				_	

- Flatness: 0.3 µm/0.000012 in (Spindle), 1.0 µm/0.00004 in (Anvil)
 Battery: SR44 (1 pc.), **938882**, for initial operational checks (standard accessory)
 Battery life: Approx. 2.4 years under normal use

- Length standard: Electromagnetic rotary sensor
 Standard accessories: Spanner (301336), 1 pc. (for maximum measuring range up to 40 mm (1.6 in)), Setting Standards for V-Anvil Micrometer


 Note: For functional details, refer to page B-7.

The models above use the same connection cables and connection units as our IP rated micrometers but these digital V-Anvil Micrometers are not IP rated.

Measurement example



Pitch Diameter Measurement of Tap by Single-wire Method



Ontional Accessories

Optional Accessories						
Order No. Type		Description				
05CZA662	В	Connecting cable (1 m)				
05CZA663	В	Connecting cable (2 m)				
06AFM380B	В	USB Input Tool Direct (2 m)				
02AZD790B	В	Connecting cables for U-WAVE-T (160 mm)				
02AZE140B	В	Connecting cables for U-WAVE-T For foot switch				
264-622	IP67	U-WAVE-TM				
264-623	Buzzer	U-WAVE-TM				
264-626	IP67	U-WAVE-TMB				
264-627	Buzzer	U-WAVE-TMB				
02AZF310	IP67/ buzzer	Connecting unit for U-WAVE-TM/TMB				

