

Micrometer

Indicating Micrometers SERIES 510

- Suitable for pass/fail judgement of mass-produced components.
- Easy to use when operating one-handed due to retractable anvil.
- In the 25 mm measuring range, the model lineup offers a choice of left or right positioning of the anvil-retraction button.
- Greatly improved accuracy: indication error and graduation of 1 μm .
- IP protection level: 54, coolant-splash resistant during grinding process.



510-121

SPECIFICATIONS

Metric												
Order No.	Range (mm)	Spindle feed error (μm)	Flatness (μm)	Parallelism (μm)	Dispersion of indication (μm)	Dial indication accuracy (μm)	Indicating range (mm)	Graduation (mm)	Dial graduation (mm)	Measuring force (N)	Anvil retraction button	Mass (g)
510-121	0 - 25	3	0.3	0.6	0.4	1	± 0.06	0.001	0.001	5 - 10	Right side	520


Inch												
Order No.	Range (in)	Spindle feed error (in)	Flatness (in)	Parallelism (in)	Dispersion of indication (in)	Dial indication accuracy (in)	Indicating range (in)	Graduation (in)	Dial graduation (in)	Measuring force (N)	Anvil retraction button	Mass (g)
510-131	0 - 1	0.00015	0.000012	0.000024	0.00002	0.00005	± 0.0023	0.0001	0.00005	5 - 10	Right side	520

• Standard Accessories: Spanner (200154), 1 pc.

DIMENSIONS

Up to 25 mm measuring range (anvil-retraction button on the right side)

Unit: mm



Range (mm)	b	d	t
0 - 25	25	31.5	16.4



Measurement example




Workpiece Stop (optional)

- Produces more stable measurement.
- Three types are available to suit workpieces of different sizes.

Unit: mm

Range	A	B
Workpiece stop A 04AZA124	$\phi 16$	23
Workpiece stop B 04AZA125	$\phi 14$	20.5
Workpiece stop C 04AZA126	$\phi 14$	15



Dmin: Minimum measurable diameter
Dmax: Maximum measurable diameter
C: Distance from the center of the workpiece to the upper surface of the workpiece stop

• Order No. 510-121, 510-141, 510-131, 510-151 Unit: mm

	Dmin	Dmax	C
Workpiece stop A	N/A	N/A	N/A
Workpiece stop B	4	16	5.0
Workpiece stop C	15	25	10.5

• 510-122 and 510-132

	Dmin	Dmax	C
Workpiece stop A	25	37	15.5
Workpiece stop B	30	42	18.0
Workpiece stop C	41	50	23.5

• 510-123 and 510-133

	Dmin	Dmax	C
Workpiece stop A	50	61	27.5
Workpiece stop B	54	66	30.0
Workpiece stop C	65	75	35.5

• 510-124 and 510-134

	Dmin	Dmax	C
Workpiece stop A	75	87	40.5
Workpiece stop B	80	92	43.0
Workpiece stop C	91	100	48.2