

THICKNESS GAUGE with COLOR SLEEVES



Please choose from white, black and green.

• For parts other than 172 series, Threaded pivot so leaves can be removed and replaced.



CS-65M (white)



CS-65M (black)



CS-65M (green)

USE • Measurement of gap width

MATERIAL

- Carbon tool steel

FEATURES

- Use for precise spacing inspection by inserting into the gap between two flat surfaces
- Indispensable for measuring the gap between piston and cylinder of automotive engine
- Leaf width 12.7mm

※ Please specify color (White, Black, Green) when ordering

Model No.	Leaf Length (mm)	Pieces/set	Size (mm)										Weight	
CS-172MA	75	9	0.30	0.04	0.05	0.06	0.07	0.08	0.10	0.15	0.20	30g		
CS-172MB	100												30g	
CS-172MC	150												50g	
CS-172MD	230												70g	
CS-172ME	300												90g	
CS-100MR	100	10	0.03	0.04	0.05	0.08	0.10	0.15	0.20	0.25	0.30	0.40	40g	
CS-150MR	150	60g												
CS-100MK	100	10	0.01	0.02	0.03	0.04	0.05	0.06	0.07	0.08	0.09	0.10	30g	
CS-150MK	150	40g												
CS-60M	75	19	0.03	0.04	0.05	0.06	0.07	0.08	0.09	0.10	0.15	0.20	60g	
CS-100MY	100													80g
CS-150MY	150													120g
CS-65M	75	25	0.03	0.04	0.05	0.06	0.07	0.08	0.09	0.10	0.11	0.12	80g	
CS-100MZ	100													100g
CS-150MZ	150													150g
CS-72M	75	12	0.04	0.05	0.06	0.07	0.08	0.10	0.15	0.20	0.30	1.00	70g	
CS-100MT	100													100g
CS-150MT	150													140g
CS-100ML	100	19	0.01	0.02	0.03	0.04	0.05	0.06	0.07	0.08	0.09	0.10	80g	
CS-150ML	150													120g
CS-80M	75	13	0.03	0.04	0.05	0.06	0.07	0.08	0.10	0.15	0.20	0.30	60g	
CS-100MX	100													90g
CS-150MX	150													140g
CS-100MH	100	10	0.10	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00	80g	
CS-150MH	150													110g

ACCURACY

Leaf size (mm)	Tolerance(mm)
0.01~0.06	±0.005
0.07~0.10	±0.01
0.11~0.35	±0.015
0.40~0.60	±0.02
0.70~3.00	±0.035

BLOCK GAUGES

PIN GAUGES

PIN VISE

PIN GAUGE ACCESSORIES

GAUGES

THREAD GAUGES

PLUG GAUGES

RING GAUGES

THICKNESS GAUGES

TAPER GAUGES

WELDING GAUGES

OTHER GAUGES